


PICS			
	model		KMD-P1580U
2.	Product identification		
	Product description		
	Cooling system (Static / Ventilated)		Ventilated
	Climate class (3= + 25°C, 60%RH)		3
	Key features		
3.	Effective Volume	(ft3)	20.8
	Effective Volume	(L)	590
	Display Area	(ft2)	28.2
	Display Area	(m²)	2.62
	Defrosting (Manual-Automatic)		Automatic
	Kind of coolant (R134a/R404a/R600a)		R290
	Foaming components		C-P
	Max noise level		Max:70
	Technical data		
4.	Voltage / frequency	V/Hz	110V/60HZ
	Temperature range	From-to, n°F	M2(30.2~44.6)
	Temperature range	From-to, n°C	M2(-1~7)
	Safety Ckass		I
	current	A	29
	Interiorinput power	W	2810
	Power consumption	KW*24H	38.66
	Aesthetics		
5.	Colour of cabinet	Steel Painting	On your option
	Inside cabinet walls	/	Coated steel
	Top plate		Coated steel
	Colour of top plate		Coated steel
	Thickness of cabinet walls	mm	40
	Material of shelves		steel plate
	Wheels/Castors/Adjustable feet	/	Adjustable feet
	Night curtain		YES
	Equipment & accessories		
6.	Defrost		YES
	Automatic evaporation of drain water		YES
	Shelves light	LED	LED
	Number of shelves		4
	Shelves (angle)		0°/9°/18°
	Digital thermostat		Dixell
	Solenoid valve		no
	Evaporator fan		YONGRONG
	Evaporator		Copper-aluminium fin
	Expansion Valve		capillary
	condenser fan		YONGRONG
	condenser		Copper-aluminium fin
	Compressor		secop*2
	Packing dimensions & loadability		
7.	Unit dimensions (W / D/ H)	inch	60"X31 1/2"X78 3/4"
	Unit dimensions (W / D/ H)	mm	1524*800*2000
	Packing dimensions (W / D/ H)(Base +frame+fumigation)	inch	65"X35"X85 7/8"
	Packing dimensions (W / D/ H)(Base +frame+fumigation)	mm	1650*890*2180
	40 ' Container load	pcs	14